




HDTV (High Definition Television) communication system









uni-directional microwave communication system


Fia. 5

microwave transceiver	decoder	LDPC coded signal decoding LDPC coded signal decoding including updating bit metric i LDPC coded modulation signal decoding including updating bit metric i LDPC decoding of a variable code rate and/or variable modulation signal		encoder	LDPC coded signal encoding	signal encoding L signal encoding L ode rate and/or variable modulation signal I	
		wireless	channel	microwave microwave tower			bi-directional microwave communication system
microwave transceiver	encoder	LDPC coded signal encoding LDPC coded modulation signal encoding Lsignal encoding LiDPC encoding of a variable code rate and/or variable modulation signal		decoder	LDPC coded signal decoding LDPC coded signal decoding including updating bit metric	signal decoding including updating bit metriciLDPC decoding of a variable code rate and/or variable modulation signal	




uni-directional point-to-point radio communication system







uni-directional communication system **Fig. 9**

					gui	1		
transceiver	decoder	OPC coded signal decodir OPC coded signal decodir ICDPC coded modulation signal decoding bit metric updating bit metric of decoding of a variable code rate and/or variable modulation signal		encoder	signal encoc	LDPC coded modulation signal encoding	OPC encoding of a variable code rate and/or variable modulation signal	
trans	ф	LDPC coded signal decoding LDPC coded signal decoding including updating bit metric LDPC coded modulation signal decoding including updating bit metric LDPC decoding of a variable code rate and/or variable		enc	LDPC coded signal encoding	LDPC code	LDPC encoding of a variable code rate and/or variable modulation signal	
						<u>'</u>	'	
				$\overline{\ \ }$	•			stem
			annel					ıtion sy
			communication channe					communica Fig. 10
			nunical					al com Fig
			COM					bi-directional communication system Fig. 10
			<u> </u>		•			bi-di
]
		coding ation ation ariable iable			coding coding metric	ation Jding ic	ariable iable	
transceiver	encoder	LDPC coded signal encoding LDPC coded modulation signal encoding LDPC encoding of a variable code rate and/or variable		decoder	LDPC coded signal decoding LDPC coded signal decoding including updating bit metric	LDPC coded modulation signal decoding including updating bit metric	LDPC decoding of a variable code rate and/or variable modulation signal	
transo	enc	coded s		dec	coded s coded s ling upda	SC coderal decoc	decodir e rate ar modulati	
		DPC LDF code				sign	cod	
		-	ا ا دُ			i i		







WLAN (Wireless Local Area Network) communication system




DSL (Digital Subscriber Line) communication system




fiber-optic communication system **Fig. 14**




satellite receiver STB (Set Top Box) system **Fig. 15**



LDPC (Low Density Parity Check) code bipartite graph **Fig. 16**





\$ 	091	£
£© 20 10 10 10 10	40 (5) (5)	

110 (2) (1) (100 (3) (3) (3)

map 0 and map 1 **Fig. 19A**

(O) (O) (O)	101 6 6 6 6	(o
010	4) 110 5)	•

(D) (D) (O) (D)	110 (7)	2)
(2)	00 G)

map 2 and map 3 **Fig. 19B**

(-) (-) (-) (-) (-) (-) (-) (-) (-) (-) (-) (-) (-) (-) (-)	101	2)
111 (2)	110 (4) (5)	3

100	101	(2
010	(4) (5) (1) (1)	

map 4 and map 5 **Fig. 20A**

(D) (O) (O)	010 011 (G)	4)
100	(4) (5) (1) (1) (1)	٠


(1)	110 (3)	(9
111 (2)	011 (4) (5) (5)	

map 6 and map 7 **Fig. 20B**


weak points at LSB

weak points at ISB


	# weak points	at MSB	2	2	2	2	2	4	4	4	4	2	2			E Di
	map		-	2	က	4	5	9	7	8	6	10	11			
\$ (-) 86	96	110 (7)	ම						100	(1)] (9		041 (2)	(11)	
101 (2)) =	(4)	<u></u>	- (d map 9 (9)	21A			110	(2)	£()	၅		(4) 49 (6) 60 (9) 40 (9) 40 (9	•	map 10 and map 11 Fig. 21B
66 86		101	©			Fig. 21A	0		010	€ 1	용()	ම		110	(10)	map 10 ar Fig.
£6 60	ව	(4)	(2))	(8)				7	56		<u></u>		10 40 11 (5)	(1	




variable signal mapping LDPC (Low Density Parity Check) coded modulation system





variable signal mapping LDPC (Low Density Parity Check) coded modulation system with code C_2






variable signal mapping LDPC (Low Density Parity Check) coded modulation system






alternative LDPC coded modulation decoding functionality using bit metric (when performing n number of iterations)

Fig. 27




LDPC (Low Density Parity Check) coded modulation decoding functionality using bit metric (with bit metric updating) Fig. 28




alternative LDPC coded modulation decoding functionality using bit metric (with bit metric updating) (when performing n number of iterations)


Fig. 29





bit decoding using bit metric (shown with respect to LDPC (Low Density Parity Check) code bipartite graph) Fig. 30A




bit decoding using bit metric updating (shown with respect to LDPC (Low Density Parity Check) code bipartite graph) Fig. 30B









method for decoding LDPC coded modulation signal with update metric (see LDPC code bipartite graph of Fig. 26B)







performance comparison of bit decoding vs. bit decoding with metric updating of LDPC (Low Density Parity Check) coded modulation signals